



Milwaukee

Antique



Performance Summary:

Heavy-duty 100% Polyurethane will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Antimicrobial agent inhibits the growth of microorganisms.

Fabric Specifications (inches)

| | |
|---------------|--------------------------------|
| Product #: | Milwaukee/Antique |
| Color: | Antique |
| Content: | 100% Polyurethane |
| Type: | PU |
| Finish: | Antimicrobial, IClean |
| Backing: | 70% polyester, 30% cotton |
| Weight: | 20.3 oz per yard |
| Width: | 54" |
| Repeat: | Horizontal: 0" Vertical: 0" |
| Roll Size: | 35 yds. |
| Intended Use: | Healthcare/Hospitality |
| Railroaded: | No |

Performance Characteristics

| | |
|------------------------------------|--|
| Abrasion Resistance ASTM D-4157 | 200,000 Double Rubs – Heavy Duty |
| Break Strength ASTM D-5034 | Warp: 98 lbs. min. Fill: 83 lbs. min. |
| Tear Strength ASTM D-2261 | Warp: 12 lbs. min. Fill: 9 lbs. min. |
| Seam Slippage ASTM D-4034 | Warp: 84 lbs. min. Fill: 85 lbs. min. |
| Brush Pilling ASTM D-3511 | Class 5 – No Pilling |
| Colorfastness to Light AATCC-16 | 200 Hours – Class 5.0 |
| Crocking AATCC-8 | Dry: Class 4.0 Wet: Class 4.0 |
| Fluid Barrier | NA |
| Antimicrobial | fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface. |

Flammability*

| | |
|------------------------|--------|
| CA 117-2013, Section 1 | Passed |
|------------------------|--------|

Cleaning & Maintenance

| | |
|--------------------|---|
| Cleaning Statement | A clean cloth, dampened with the appropriate cleaning solution, should be applied to affected areas as soon as possible. Clean spots or stains from the outside to the middle of the affected area to prevent circling. 1. Soap and water 2. Difficult stains use Fantastik® or Formula 409® 3. Disinfects with 5:1 water / bleach solution |
| Cleaning Code | W |

Warranty

1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

1-800-889-3957 maxwellthomas.com



Milwaukee

Sepia



Performance Summary:

Heavy-duty 100% Polyurethane will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Antimicrobial agent inhibits the growth of microorganisms.

Fabric Specifications (inches)

| | |
|---------------|--------------------------------|
| Product #: | Milwaukee/Sepia |
| Color: | Sepia |
| Content: | 100% Polyurethane |
| Type: | PU |
| Finish: | Antimicrobial, IClean |
| Backing: | 70% polyester, 30% cotton |
| Weight: | 20.3 oz per yard |
| Width: | 54" |
| Repeat: | Horizontal: 0" Vertical: 0" |
| Roll Size: | 35 yds. |
| Intended Use: | Healthcare/Hospitality |
| Railroaded: | No |

Performance Characteristics

| | |
|------------------------------------|--|
| Abrasion Resistance ASTM D-4157 | 200,000 Double Rubs – Heavy Duty |
| Break Strength ASTM D-5034 | Warp: 98 lbs. min. Fill: 83 lbs. min. |
| Tear Strength ASTM D-2261 | Warp: 12 lbs. min. Fill: 9 lbs. min. |
| Seam Slippage ASTM D-4034 | Warp: 84 lbs. min. Fill: 85 lbs. min. |
| Brush Pilling ASTM D-3511 | Class 5 – No Pilling |
| Colorfastness to Light AATCC-16 | 200 Hours – Class 5.0 |
| Crocking AATCC-8 | Dry: Class 4.0 Wet: Class 4.0 |
| Fluid Barrier | NA |
| Antimicrobial | fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface. |

Flammability*

| | |
|------------------------|--------|
| CA 117-2013, Section 1 | Passed |
|------------------------|--------|

Cleaning & Maintenance

| | |
|--------------------|---|
| Cleaning Statement | A clean cloth, dampened with the appropriate cleaning solution, should be applied to affected areas as soon as possible. Clean spots or stains from the outside to the middle of the affected area to prevent circling. 1. Soap and water 2. Difficult stains use Fantastik® or Formula 409® 3. Disinfects with 5:1 water / bleach solution |
| Cleaning Code | W |

Warranty

1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

1-800-889-3957 maxwellthomas.com