

Gillingham

Antique



Performance Summary:

Heavy-duty 83.30% Olefin, 16.70% Polyester Crypton® Non-PFOA Soil & Stain Protection will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

Fabric Specifications (inches)

Product #:	KW-10300.6642CAT
Color:	Antique
Content:	83.30% Olefin, 16.70% Polyester
Type:	Woven
Finish:	Crypton® Non-PFOA Soil & Stain Protection
Backing:	Crypton® Fluid Barrier
Weight:	13.795 oz./sq. yd. +1.0
Width:	56"
Repeat:	Horizontal: 7.125" Vertical: 9.333"
Roll Size:	55 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	Yes

Performance Characteristics

Abrasion Resistance ASTM D-4157	63,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 115 lbs. min. Fill: 197 lbs. min.
Tear Strength ASTM D-2261	Warp: 18 lbs. min. Fill: 31 lbs. min.
Seam Slippage ASTM D-4034	Warp: 115 lbs. min. Fill: 72 lbs. min.
Brush Pilling ASTM D-3511	Class 3.0
Colorfastness to Light AATCC-16	40 Hours – Class 4.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	Crypton® integrated fluid barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

Flammability*

CA 117-2013, Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

Cleaning & Maintenance

Cleaning Statement	Spot clean with soap and water
Cleaning Code	(W)

Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	--

Warranty

1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

Gillingham

Diversion



Performance Summary:

Heavy-duty 83.30% Olefin, 16.70% Polyester Crypton® Non-PFOA Soil & Stain Protection will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

Fabric Specifications (inches)

Product #:	KW-10300.6642CAB
Color:	Diversion
Content:	83.30% Olefin, 16.70% Polyester
Type:	Woven
Finish:	Crypton® Non-PFOA Soil & Stain Protection
Backing:	Crypton® Fluid Barrier
Weight:	13.795 oz./sq. yd. +1.0
Width:	56"
Repeat:	Horizontal: 7.125 inches Vertical: 9.333 inches
Roll Size:	55 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	Yes

Performance Characteristics

Abrasion Resistance ASTM D-4157	63,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 115 lbs. min. Fill: 197 lbs. min.
Tear Strength ASTM D-2261	Warp: 18 lbs. min. Fill: 31 lbs. min.
Seam Slippage ASTM D-4034	Warp: 115 lbs. min. Fill: 72 lbs. min.
Brush Pilling ASTM D-3511	Class 3.0
Colorfastness to Light AATCC-16	40 Hours – Class 4.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	Crypton® integrated fluid barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

Flammability*

CA 117-2013, Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

Cleaning & Maintenance

Cleaning Statement	Spot clean with soap and water
Cleaning Code	(W)

Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	--

Warranty

1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

Gillingham

Beguiled



Performance Summary:

Heavy-duty 83.30% Olefin, 16.70% Polyester Crypton® Non-PFOA Soil & Stain Protection will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

Fabric Specifications (inches)

Product #:	KW-10300.6642CAC
Color:	Beguiled
Content:	83.30% Olefin, 16.70% Polyester
Type:	Woven
Finish:	Crypton® Non-PFOA Soil & Stain Protection
Backing:	Crypton® Fluid Barrier
Weight:	13.795 oz./sq. yd. +1.0
Width:	56 inches
Repeat:	Horizontal: 7.125" Vertical: 9.333"
Roll Size:	55 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	Yes

Performance Characteristics

Abrasion Resistance ASTM D-4157	63,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 115 lbs. min. Fill: 197 lbs. min.
Tear Strength ASTM D-2261	Warp: 18 lbs. min. Fill: 31 lbs. min.
Seam Slippage ASTM D-4034	Warp: 115 lbs. min. Fill: 72 lbs. min.
Brush Pilling ASTM D-3511	Class 3.0
Colorfastness to Light AATCC-16	40 Hours – Class 4.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	Crypton® integrated fluid barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

Flammability*

CA 117-2013, Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

Cleaning & Maintenance

Cleaning Statement	Spot clean with soap and water
Cleaning Code	(W)

Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	--

Warranty

1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks