

# Maxwell Thomas®

By Direct Supply

## Lavinia

Cerulean



### Performance Summary:

Heavy-duty 100% POLYESTER FR NANOTEX will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

### Fabric Specifications (inches)

Product #:	KP-10329.7562Teal
Color:	Cerulean
Content:	100% POLYESTER FR
Type:	Print
Finish:	NANOTEX
Backing:	NANOGUARD moisture barrier
Weight:	12.61 oz./yd.
Width:	54"
Repeat:	Horizontal: 27" Vertical: 25"
Roll Size:	60 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	No

### Performance Characteristics

Abrasion Resistance ASTM D-4157	Exceeds 30,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 308 lbs. min. Fill: 162 lbs. min.
Tear Strength ASTM D-2261	Warp: 60 lbs. min. Fill: 49 lbs. min.
Seam Slippage ASTM D-4034	Warp: 74 lbs. min. Fill: 59 lbs. min.
Brush Pilling ASTM D-3511	Class 5 – No Pilling
Colorfastness to Light AATCC-16	40 Hours – Class 5.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	NANOGUARD integrated fluid barrier
Antimicrobial	NANOTEX fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

### Flammability\*

CA 117-2013, Section 1	Passed
------------------------	--------

### Cleaning & Maintenance

Cleaning Statement	Spot clean using a mild water-free solvent or dry cleaning product
Cleaning Code	S

### Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	---

### Warranty 1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

# Maxwell Thomas®

By Direct Supply

## Lavinia

Sebastian



### Performance Summary:

Heavy-duty 100% POLYESTER FR NANOTEX will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

### Fabric Specifications (inches)

Product #:	KP-10329.7562Brick
Color:	Sebastian
Content:	100% POLYESTER FR
Type:	Print
Finish:	NANOTEX
Backing:	NANOGUARD moisture barrier
Weight:	12.61 oz./yd.
Width:	54"
Repeat:	Horizontal: 27" Vertical: 25"
Roll Size:	60 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	No

### Performance Characteristics

Abrasion Resistance ASTM D-4157	Exceeds 30,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 308 lbs. min. Fill: 162 lbs. min.
Tear Strength ASTM D-2261	Warp: 60 lbs. min. Fill: 49 lbs. min.
Seam Slippage ASTM D-4034	Warp: 74 lbs. min. Fill: 59 lbs. min.
Brush Pilling ASTM D-3511	Class 5 – No Pilling
Colorfastness to Light AATCC-16	40 Hours – Class 5.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	NANOGUARD integrated fluid barrier
Antimicrobial	NANOTEX fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

### Flammability\*

CA 117-2013, Section 1	Passed
------------------------	--------

### Cleaning & Maintenance

Cleaning Statement	Spot clean using a mild water-free solvent or dry cleaning product
Cleaning Code	S

### Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	---

### Warranty 1 Year

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks