

## Steele City

Cardimom



### Performance Summary:

Heavy-duty 73.89% Olefin, 26.11% Polyester Crypton® Non-PFOA Soil & Stain Protection will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

### Fabric Specifications (inches)

Product #:	KW-10303.6641CAG
Color:	Cardimom
Content:	73.89% Olefin, 26.11% Polyester
Type:	Woven
Finish:	Crypton® Non-PFOA Soil & Stain Protection
Backing:	Crypton® Fluid Barrier
Weight:	9.658 oz./sq. yd. +1.0
Width:	54"
Repeat:	Horizontal: 6.938" Vertical: 6.75"
Roll Size:	55 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	Yes

### Performance Characteristics

Abrasion Resistance ASTM D-4157	51,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 97 lbs. min. Fill: 123 lbs. min.
Tear Strength ASTM D-2261	Warp: 13 lbs. min. Fill: 14 lbs. min.
Seam Slippage ASTM D-4034	Warp: 107 lbs. min. Fill: 59 lbs. min.
Brush Pilling ASTM D-3511	Class 4.0
Colorfastness to Light AATCC-16	40 Hours – Class 4.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	Crypton® integrated fluid barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

### Flammability\*

CA 117-2013, Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

### Cleaning & Maintenance

Cleaning Statement	Solvent or spot clean
Cleaning Code	(WS)

### Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	--

### Warranty

**1 Year**

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

## Steele City

Noble



### Performance Summary:

Heavy-duty 73.89% Olefin, 26.11% Polyester Crypton® Non-PFOA Soil & Stain Protection will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

### Fabric Specifications (inches)

Product #:	KW-10303.6641CAB
Color:	Noble
Content:	73.89% Olefin, 26.11% Polyester
Type:	Woven
Finish:	Crypton® Non-PFOA Soil & Stain Protection
Backing:	Crypton® Fluid Barrier
Weight:	9.658 oz./sq. yd. +1.0
Width:	54"
Repeat:	Horizontal: 6.938" Vertical: 6.75"
Roll Size:	55 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	Yes

### Performance Characteristics

Abrasion Resistance ASTM D-4157	51,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 97 lbs. min. Fill: 123 lbs. min.
Tear Strength ASTM D-2261	Warp: 13 lbs. min. Fill: 14 lbs. min.
Seam Slippage ASTM D-4034	Warp: 107 lbs. min. Fill: 59 lbs. min.
Brush Pilling ASTM D-3511	Class 4.0
Colorfastness to Light AATCC-16	40 Hours – Class 4.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	Crypton® integrated fluid barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

### Flammability\*

CA 117-2013, Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

### Cleaning & Maintenance

Cleaning Statement	Solvent or spot clean
Cleaning Code	(WS)

### Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	--

### Warranty

**1 Year**

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks

## Steele City

Gallant



### Performance Summary:

Heavy-duty 73.89% Olefin, 26.11% Polyester Crypton® Non-PFOA Soil & Stain Protection will hold up to years of use. Enhanced resistance to soil, stains and abrasions for extra durability. Fluid barrier repels liquids. Antimicrobial agent inhibits the growth of microorganisms. Bleach-solution cleanable for easier cleaning.

### Fabric Specifications (inches)

Product #:	KW-10303.6641CAC
Color:	Gallant
Content:	73.89% Olefin, 26.11% Polyester
Type:	Woven
Finish:	Crypton® Non-PFOA Soil & Stain Protection
Backing:	Crypton® Fluid Barrier
Weight:	9.658 oz./sq. yd. +1.0
Width:	54"
Repeat:	Horizontal: 6.938" Vertical: 6.75"
Roll Size:	55 yds.
Intended Use:	Healthcare/Hospitality
Railroaded:	Yes

### Performance Characteristics

Abrasion Resistance ASTM D-4157	51,000 Double Rubs – Heavy Duty
Break Strength ASTM D-5034	Warp: 97 lbs. min. Fill: 123 lbs. min.
Tear Strength ASTM D-2261	Warp: 13 lbs. min. Fill: 14 lbs. min.
Seam Slippage ASTM D-4034	Warp: 107 lbs. min. Fill: 59 lbs. min.
Brush Pilling ASTM D-3511	Class 4.0
Colorfastness to Light AATCC-16	40 Hours – Class 4.0
Crocking AATCC-8	Dry: Class 4.0 Wet: Class 3.0
Fluid Barrier	Crypton® integrated fluid barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface

### Flammability\*

CA 117-2013, Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

### Cleaning & Maintenance

Cleaning Statement	Solvent or spot clean
Cleaning Code	(WS)

### Environmental

GreenGuard	Third-Party GREENGUARD Select Certified
------------	--

### Warranty

**1 Year**

Please order samples prior to purchase – the colors of fabrics on our website may vary slightly compared to the actual product.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.



ACT® Registered Certification Marks