







# Fontenelle LED Overbed

#### Features:

The Fontenelle overbed is a contemporary style with natural wood accent for any indoor décor wall mount application. This fixture is suitable for horizontal wall mount in vast areas. Conveniently integrated pull chain switches are essential to operate nightlight, up light and down light to meet any tasks.

#### Construction

The housing is die formed from 22-gauge steel and is provided with standard mounting holes and wiring access.

### **Finish**

Natural wood accent in espresso or weathered gray finish.

## Diffuser

The top and bottom diffuser is made from 0.10" white acrylic sheet. The front and sides are double laminated. Lumafuse $^{\text{M}}$  fabric in jute or linen white.

#### **Electrical**

Input 120VAC / 60 Hz, 0.7A max. Not compatible with dimmers.

#### **LED**

Integrated LED modules capable of producing a total of 4050 source lumens for 38" or 5400 source lumens for 50" in 3000K CCT. Rated for 50.000 hours and 90 CRI.

## Certification

cETLus listed for damp locations. ADA compliant.

## **Options**

4-way pull switch or wall switch (refer to Ordering Information below).

## Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

## **Ordering Information:**

Espresso/Jute	Weathered Gray/Jute	LED	Source Lumens	CCT	Features	L	Н	D
#L9972	#L9973	60W	1350 up/2700 down	3000K	4-Way Pull Switch	38½"	41/4"	4"
#L9974	#L9975	60W	1350 up/2700 down	3000K	Wall Switch	38½"	4¼"	4"
#L9976	#L9977	80W	1800 up/3600 down	3000K	4-Way Pull Switch	50½"	41/4"	4"
#1 9978	#1 9979	80\//	1800 up/3600 down	3000K	Wall Switch	501/2"	41/4"	4"

Espresso/ Linen White	Weathered Gray/ Linen White	LED	Source Lumens	ССТ	Features	L	н	D
#L9964	#L9965	60W	1350 up/2700 down	3000K	4-Way Pull Switch	38½"	41/4"	4"
#L9966	#L9967	60W	1350 up/2700 down	3000K	Wall Switch	38½"	4¼"	4"
#L9968	#L9969	80W	1800 up/3600 down	3000K	4-Way Pull Switch	50½"	4¼"	4"
#L9970	#L9971	80W	1800 up/3600 down	3000K	Wall Switch	50½"	4¼"	4"

<sup>\*</sup> Specifications and dimensions subject to change without notice